

# Recent Applications and Algorithm Development Using FUN3D



Eric J. Nielsen  
Computational AeroSciences Branch  
NASA Langley Research Center











VT AOE '94, '98



# FUN3D Core Capabilities


<http://fun3d.larc.nasa.gov>

- Established as a research code in late 1980's; now supports numerous internal and external efforts across the speed range
- Solves 2D/3D steady and unsteady Euler and RANS equations on node-based mixed element grids for compressible and incompressible flows
- General dynamic mesh capability: any combination of rigid / overset / morphing grids, including 6-DOF effects
- Aeroelastic modeling using mode shapes, full FEM, CC, etc.
- Constrained / multipoint adjoint-based design and mesh adaptation
- Distributed development team using agile/extreme software practices including 24/7 regression, performance testing
- Capabilities fully integrated, online documentation, training videos, tutorials





# Towards Physics-Based Design



HPC-related milestones in red

★ Internationally-unique capability



# ***FUN3D User Base***

- Widely used across multiple industries
  - Aerospace, automotive, computing...
- Other government agencies
  - DoD, DoE, FAA...
- Also individuals, small businesses, research groups
- Has been used by hundreds of universities
  - Over 60 students have interned with the team or conducted thesis work using FUN3D: 20 MS and PhD theses generated
  - Graduates with hands-on FUN3D experience are highly sought after





# Team-Oriented Development

**Team-oriented** strategy is critical

- Broad expertise necessary for broad success
- High *truck* number

Pair programming boosts *truck* number, improves code quality


Weekly scrums

- Very quick summary of “Did, Do, In-the-Way”
- Scrum master notes impediments
- No “Death by PowerPoint”
- Management may attend but cannot talk

Automated testing of repository commits

- Every commit screened for adherence to coding standard
- Each commit triggers a series of regression tests
- Successful gauntlet means FUN3D is safe to ship


Jennifer Abras  
Natalia Alexandrov  
Kyle Anderson  
Bala Balakumar  
Bob Bartels  
Karen Bibb  
Bob Biedron  
Alejandro Campos  
Jan-Renee Carlson  
Mark Carpenter  
Joe Derlaga  
Boris Diskin  
Austen Duffy  
Peter Gnoffo  
Dana Hammond  
Clara Helm  
Bill Jones  
Bil Kleb  
Beth Lee-Rausch  
Eric Lynch  
Steve Massey  
Eric Nielsen  
Hiro Nishikawa  
Dave O'Brien  
Mike Park  
Sriram Rallabhandi  
Shatra Reehal  
Chris Rumsey  
Rajiv Shenoy  
Marilyn Smith  
Jim Thomas  
Veer Vatsa  
David Venditti  
Jeff White  
Bill Wood  
Kan Yang





# ***FUN3D and High Performance Computing***

***FUN3D is used on a broad range of HPC installations around the country***





***Scaled to 80,000 cores on DoE's Cray XK7 'Titan'***  
***using grids containing billions of elements***  
***Awarded the prestigious Gordon Bell Prize in a***  
***past collaboration with Argonne National Lab***



# Motivation for HPC

## Airframe Noise Challenge Problem

*Images Courtesy NASA/Gulfstream Partnership  
Effort on Airframe Noise Research*



### Semi-span Aircraft in High-Lift Configuration

- Current simulations use ~1B elements
- Computation takes ~4 months on 3000 cores; represents ~0.3 seconds of real time
- Would like to run at least 100x larger spatial mesh, much finer temporal mesh, with much longer physical durations (exp avgs over ~15 seconds)
- Single solution would require 6,750x more CPU time (2,250 years wall-clock) in current environment
- Numerous solutions ultimately needed for parametric studies, open/closed tunnel configs, etc.





# Across NASA Missions

*FUN3D supplies critical physics-based aerodynamics for a broad range of applications across all Mission Directorates*

## Science


Phoenix



Mars Science Lab



InSight



Curiosity



*"The FUN3D team has developed a capability that continues to find new and unique applications of significant importance to the agency."*


- Dave Schuster

NASA Technical Fellow for Aerosciences


NASA Engineering and Safety Center

## Human Exploration and Operations


SLS



Orion



STS



Ares










# Across NASA Missions

## Space Technology


Launch Abort



Supersonic Retropropulsion




IRVE




Rotorcraft




Sonic Boom Mitigation



## Aeronautics Research




Airframe Noise



*Due to increased demand from NASA scientists and engineers, FUN3D simulations now account for the single largest block of supercomputing cycles at the Agency: 12% of NAS, or approximately 200 million hours per year*




# ***Hypersonic Inflatable Aerodynamic Decelerators***



***HIAD devices offer a lightweight option for decelerating very large masses from hypersonic speeds***




***Aeroelastic computations are used to predict performance characteristics***







# ***Designing the Space Launch System***





***Thousands of simulations are being performed  
to develop NASA's newest launch vehicle***




# ***Mars Ascent Vehicle***

***A vehicle like this  
will be used to return  
a sample from the  
Martian surface***




***Courtesy  
Ashley Korzun***







# ***Supersonic Nozzle Design***



*Courtesy  
Chris Heath*


***FUN3D's unique adjoint-based design capability is  
being used to mitigate sonic boom effects***



# ***SUGAR Truss-Braced Wing***




*Courtesy  
Bob Bartels*



***Aeroelastic Analysis of  
the Boeing SUGAR  
Truss-Braced Wing  
Concept***



# ***Distributed Electric Propulsion***



*Courtesy  
Mike Park,  
Sally Viken,  
Karen Deere,  
Mark Moore*

***DEP offers vastly improved efficiencies  
for regional vehicles***








# ***Distributed Electric Propulsion***

***NASA will test a truck-mounted  
concept in November***



***Courtesy  
Mike Park, Sally Viken,  
Karen Deere, Mark Moore***






# ***FUN3D and High-Order Methods***

***Raising the Bar for CFD***

- High-order methods have failed to penetrate production aerodynamics due to robustness issues
- Entropy-stable approaches offer mathematical guarantees on stability
  - If implemented correctly, the code will never “blow up”
  - Nature is stable, so our discretizations should be also
- No dealiasing, artificial dissipation, or filtering necessary
- Being developed as a library for FUN3D


## ***Standard Second-Order Finite Volume Scheme***

- 137,060 DOFs
- Shows mild spanwise variations very late



## ***Entropy-Stable Scheme $p = 5$ (sixth order)***

- 29,066,688 DOFs
- Good qualitative resolution of expected flow physics





# Across the Aerospace Industry

## SPACEX

First private company to achieve orbit  
and dock with the International Space Station

**Primary aerodynamics tool: FUN3D**

- FUN3D used for extensive analysis of Falcon 1 and Falcon 9 rockets, Dragon spacecraft
- Team consults frequently and provides new features and capabilities as requested

*"The FUN3D software suite and development team have enabled SpaceX to rapidly design, build, and successfully fly a new generation of rockets and spacecraft."*

- Justin Richeson  
Manager, SpaceX Aerodynamics





# At the Department of Defense




IA-407



- AMRDEC at Redstone Arsenal**
- **Troop safety:** airworthiness qualification
  - **Dramatic cost savings:** fewer tunnel & flight tests
  - Intense demand for timely results on massive computing systems
  - Decade of use in direct support of the US warfighter




CH-47



## Air Force Research Lab

- Funded on-site training workshop (20 students)



V-22

## NAVAIR at Patuxent River

- Hosted on-site training workshop
- Hired two recent Georgia Tech PhD grads
- FUN3D development for theses








# Outside Aerospace





- Ford Motor Sports used FUN3D for improving rear wings for road races and the Indy 500
- Newman/Haas Team: Michael Andretti, Christian Fittipaldi
- Team Rahal: Bobby Rahal, Bryan Herta, and Max Papis
- Real-time designs tested and installed on cars within two weeks



- Used FUN3D on world's largest supercomputer to perform the most advanced truck simulations ever attempted
- Developed add-on kits that improve fuel mileage by as much as 11%
- Spin-off company has sold over 40,000 units
- Covered by print and TV news

*"FUN3D is a national asset."*  
- Mike Henderson,  
BMI Founder





# ***The Steady Adjoint Equations***

## ***Notation and Governing Equations***

We wish to perform rigorous adaptation and design optimization based on the steady-state Euler/Navier-Stokes equations, ***without requiring any a priori knowledge of the problem:***

$$\frac{\partial \mathbf{Q}}{\partial t} + \mathbf{R}(\mathbf{D}, \mathbf{Q}, \mathbf{X}) = 0$$

**R** = Spatial residual

**Q** = Dependent variables

**D** = Design variables

**X** = Computational grid

- Incompressible through hypersonic flows
- May include turbulence models and various physical models from perfect gas through thermochemical nonequilibrium



# The Steady Adjoint Equations

Combine cost function with Lagrange multipliers  $\Lambda$ :

$$L(\mathbf{D}, \mathbf{Q}, \mathbf{X}, \Lambda_f, \Lambda_g) = \underbrace{f(\mathbf{D}, \mathbf{Q}, \mathbf{X})}_{\text{Cost Function}} + \underbrace{\Lambda_f^T \mathbf{R}(\mathbf{D}, \mathbf{Q}, \mathbf{X})}_{\text{Flowfield Equations}} + \underbrace{\Lambda_g^T (\mathbf{K}\mathbf{X} - \mathbf{X}_{surf})}_{\text{Mesh Movement Equations}}$$

$f$  = Cost function (lift/drag/boom/etc)

$\Lambda_f$  = Flowfield adjoint variable

$\mathbf{K}$  = Mesh movement elasticity matrix

$\Lambda_g$  = Grid adjoint variable

Differentiate with respect to  $\mathbf{D}$ :

$$\begin{aligned} \frac{dL}{d\mathbf{D}} = \frac{\partial f}{\partial \mathbf{D}} + \left[ \frac{\partial \mathbf{R}}{\partial \mathbf{D}} \right]^T \Lambda_f + \left[ \frac{\partial \mathbf{Q}}{\partial \mathbf{D}} \right]^T \left\{ \frac{\partial f}{\partial \mathbf{Q}} + \left[ \frac{\partial \mathbf{R}}{\partial \mathbf{Q}} \right]^T \Lambda_f \right\} \\ + \left[ \frac{\partial \mathbf{X}}{\partial \mathbf{D}} \right]^T \left\{ \frac{\partial f}{\partial \mathbf{X}} + \left[ \frac{\partial \mathbf{R}}{\partial \mathbf{X}} \right]^T \Lambda_f + \Lambda_g^T \mathbf{K} \right\} - \Lambda_g^T \left[ \frac{\partial \mathbf{X}}{\partial \mathbf{D}} \right]_{surf} \end{aligned}$$

$$\longrightarrow \underbrace{\left[ \frac{\partial \mathbf{R}}{\partial \mathbf{Q}} \right]^T}_{\text{Governing Eqns}} \Lambda_f = - \underbrace{\frac{\partial f}{\partial \mathbf{Q}}}_{\text{Engineering Output}}$$

This adjoint equation for the flowfield has powerful implications for:

- Error estimation & mesh adaptation
- Sensitivity analysis





# *The Steady Adjoint Equations*

## *Error Estimation and Mesh Adaptation*

It is apparent that:

$$\Lambda_f \equiv \frac{\partial f}{\partial \mathbf{R}}$$




*Direct relationship between local equation error and the output we are interested in*

- These relationships can be used to get error estimates on  $f$
- Also used to compute a scalar field explicitly relating local point spacing requirements to output accuracy for a user-specified error tolerance
- Often yields non-intuitive insight into gridding requirements
- Relies on underlying mathematics to adapt, rather than heuristics such as solution gradients

### Transonic Wing-Body:

*“Where do I need to put grid points to get 10 drag counts of accuracy?”*



**Blue=Sufficient Resolution**

**Red=Under-Resolved**

User no longer required to be a CFD expert to get the right answer



# *The Steady Adjoint Equations*

## *Sensitivity Analysis*

Examine the remaining terms in the linearization:

$$\frac{dL}{d\mathbf{D}} = \frac{\partial f}{\partial \mathbf{D}} + \left[ \frac{\partial \mathbf{R}}{\partial \mathbf{D}} \right]^T \Lambda_f + \left[ \frac{\partial \mathbf{X}}{\partial \mathbf{D}} \right]^T \left\{ \frac{\partial f}{\partial \mathbf{X}} + \left[ \frac{\partial \mathbf{R}}{\partial \mathbf{X}} \right]^T \Lambda_f + \Lambda_g^T \mathbf{K} \right\} - \Lambda_g^T \left[ \frac{\partial \mathbf{X}}{\partial \mathbf{D}} \right]_{surf}$$

$$\longrightarrow \mathbf{K}^T \Lambda_g = - \left\{ \frac{\partial f}{\partial \mathbf{X}} + \left[ \frac{\partial \mathbf{R}}{\partial \mathbf{X}} \right]^T \Lambda_f \right\} \quad \text{Discrete adjoint equation for mesh movement}$$

$$\longrightarrow \frac{dL}{d\mathbf{D}} = \frac{\partial f}{\partial \mathbf{D}} + \Lambda_f^T \frac{\partial \mathbf{R}}{\partial \mathbf{D}} - \Lambda_g^T \left[ \frac{\partial \mathbf{X}}{\partial \mathbf{D}} \right]_{surf} \quad \text{Sensitivity equation}$$

### Function Evaluation

1. Compute surface mesh at current  $\mathbf{D}$
2. Solve mesh movement equations
3. Solve flowfield equations

### Sensitivity Evaluation

3. Solve flowfield adjoint equations
2. Solve mesh adjoint equations
1. Matrix-vector product over surface

**Analysis Cost = Sensitivity Analysis Cost**

Even for *1000's* of design variables



# Deriving the Unsteady Adjoints

$$\begin{aligned}
 L(\mathbf{D}, \mathbf{Q}, \mathbf{X}, \boldsymbol{\Lambda}, \boldsymbol{\Lambda}_g) = & f\Delta t + \sum_{n=1}^N [\boldsymbol{\Lambda}_g^n]^T \mathbf{G}^n \Delta t \\
 & + \sum_{n=1}^N \left\{ [\mathbf{C}_s^n \circ \boldsymbol{\Lambda}_s^n]^T \left[ a \frac{\mathbf{Q}_s^n - \mathbf{I}_s^n \mathbf{Q}^{n-1}}{\Delta t} \circ \mathbf{V}_s^n \right. \right. \\
 & + c \frac{\mathbf{I}_s^n \mathbf{Q}^{n-2} - \mathbf{I}_s^n \mathbf{Q}^{n-1}}{\Delta t} \circ (\mathbf{I}_s^n \mathbf{V}^{n-2}) \\
 & \left. \left. + d \frac{\mathbf{I}_s^n \mathbf{Q}^{n-3} - \mathbf{I}_s^n \mathbf{Q}^{n-1}}{\Delta t} \circ (\mathbf{I}_s^n \mathbf{V}^{n-3}) \right] \right. \\
 & + [\boldsymbol{\Lambda}_s^n]^T [\mathbf{R}^n + ((\mathbf{I}_s^n \mathbf{Q}^{n-1}) \circ \mathbf{C}_s^n + \beta \bar{\mathbf{C}}_s^n) \circ \mathbf{R}_{\text{GCL}}^n] \\
 & \left. + [\boldsymbol{\Lambda}_f^n]^T [\mathbf{A}^n \mathbf{Q}^n] + [\boldsymbol{\Lambda}_h^n]^T [\mathbf{P}^n \mathbf{Q}^n] \right\} \Delta t \\
 & + (f^0 + [\boldsymbol{\Lambda}_g^0]^T \mathbf{G}^0 + [\boldsymbol{\Lambda}^0]^T \mathbf{R}^{\text{in}}) \Delta t
 \end{aligned}$$

- Flow field and grid adjoint equations derived for the time-dependent Navier-Stokes equations on arbitrary combinations of static/rigidly moving/deforming overset grids undergoing parent-child motion
- The following terms are included in the Lagrangian
  - Objective function
  - Grid terms
  - Higher-order temporal terms
  - Fluxes
  - Geometric Conservation Law term
  - Overset interpolation terms
  - Initial conditions
- Implemented by hand and verified using complex variables

◦ is the Hadamard vector multiplication operator; see

Nielsen, E.J. and Diskin, B., "Discrete Adjoint-Based Design for Unsteady Turbulent Flows on Dynamic Overset Unstructured Grids," AIAA Journal, Vol. 51, No. 6, June 2013.



# The Unsteady Adjoint Equations

1370

NIELSEN AND DISKIN

$$\begin{aligned} C_s^n \cdot \left[ a \frac{Q_s^n - I_s^n Q^{n-1}}{\Delta t} \cdot V_s^n + c \frac{I_s^n Q^{n-2} - I_s^n Q^{n-1}}{\Delta t} \cdot I_s^n V^{n-2} \right. \\ \left. + d \frac{I_s^n Q^{n-3} - I_s^n Q^{n-1}}{\Delta t} \cdot I_s^n V^{n-3} \right] \\ + R^n + ((I_s^n Q^{n-1}) \cdot C_s^n + \beta \tilde{C}_s^n) \cdot R_{GCL}^n = 0 \end{aligned} \quad (A1)$$

Proceeding as before, the Lagrangian can be written as

$$\begin{aligned} L(D, Q, X, \Lambda, A_s) = f \Delta t + \sum_{n=1}^N [\Lambda_s^n]^T G^n \Delta t \\ + \sum_{n=1}^N \left\{ [C_s^n \cdot \Lambda_s^n]^T \left[ a \frac{Q_s^n - I_s^n Q^{n-1}}{\Delta t} \cdot V_s^n \right. \right. \\ \left. \left. + c \frac{I_s^n Q^{n-2} - I_s^n Q^{n-1}}{\Delta t} \cdot (I_s^n V^{n-2}) \right. \right. \\ \left. \left. + d \frac{I_s^n Q^{n-3} - I_s^n Q^{n-1}}{\Delta t} \cdot (I_s^n V^{n-3}) \right] \right. \\ \left. + [\Lambda_s^n]^T [R^n + ((I_s^n Q^{n-1}) \cdot C_s^n + \beta \tilde{C}_s^n) \cdot R_{GCL}^n] \right. \\ \left. + [\Lambda_s^n]^T [\Lambda^n Q^n] + [\Lambda_s^n]^T [P^n Q^n] \right\} \Delta t \\ + (f^0 + [\Lambda_s^0]^T G^0 + [\Lambda_s^0]^T R^{in}) \Delta t \end{aligned} \quad (A2)$$

On time levels 1 and 2, the time derivatives are assumed to be discretized with the BDF1 and BDF2 schemes, respectively. Taking into account the dependencies on data at time levels  $n-2$  and  $n-3$ , the adjoint equations are obtained as follows:

$$\begin{aligned} S: \\ \frac{a}{\Delta t} V_s^n \cdot C_s^n \cdot \Lambda_s^n + \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T \\ - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{a}{\Delta t} V_s^{n+1} - \frac{c}{\Delta t} I_s^{n+1} V^{n-1} - \frac{d}{\Delta t} I_s^{n+1} V^{n-2} \right. \right. \right. \\ \left. \left. + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \end{aligned}$$

$$\begin{aligned} F: \\ \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T \\ - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{a}{\Delta t} V_s^{n+1} - \frac{c}{\Delta t} I_s^{n+1} V^{n-1} - \frac{d}{\Delta t} I_s^{n+1} V^{n-2} \right. \right. \right. \\ \left. \left. + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \end{aligned}$$

$$\begin{aligned} H: \\ \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T \\ - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{a}{\Delta t} V_s^{n+1} - \frac{c}{\Delta t} I_s^{n+1} V^{n-1} - \frac{d}{\Delta t} I_s^{n+1} V^{n-2} \right. \right. \right. \\ \left. \left. + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \end{aligned} \quad (A3)$$

for  $3 \leq n \leq N$

$$\begin{aligned} S: \\ \frac{3}{2\Delta t} V_s^n \cdot C_s^n \cdot \Lambda_s^n + \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = \\ - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{a}{\Delta t} V_s^{n+1} - \frac{c}{\Delta t} I_s^{n+1} V^{n-1} \right. \right. \right. \\ \left. \left. - \frac{d}{\Delta t} I_s^{n+1} V^{n-2} + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] \\ \left. + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \\ F: \\ \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T \\ - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{a}{\Delta t} V_s^{n+1} - \frac{c}{\Delta t} I_s^{n+1} V^{n-1} - \frac{d}{\Delta t} I_s^{n+1} V^{n-2} \right. \right. \right. \\ \left. \left. + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \end{aligned}$$

$$\begin{aligned} H: \\ \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T \\ - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{a}{\Delta t} V_s^{n+1} - \frac{c}{\Delta t} I_s^{n+1} V^{n-1} - \frac{d}{\Delta t} I_s^{n+1} V^{n-2} \right. \right. \right. \\ \left. \left. + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \end{aligned} \quad (A4)$$

$$\begin{aligned} S: \\ \frac{1}{\Delta t} V_s^n \cdot C_s^n \cdot \Lambda_s^n + \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = \\ - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{3}{2\Delta t} V_s^{n+1} \right. \right. \right. \\ \left. \left. - \frac{1}{2\Delta t} I_s^{n+1} V^{n-1} + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] \\ \left. + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \end{aligned}$$

$$\begin{aligned} F: \\ \left[ \frac{\partial R^n}{\partial Q_s^n} \right]^T \Lambda_s^n + [\Lambda_s^n]^T \Lambda_s^n + [P_s^n]^T \Lambda_s^n = - \left[ \frac{\partial f}{\partial Q_s^n} \right]^T \\ - I_s^n \left\{ [I_s^{n+1}]^T \left[ \left( -\frac{3}{2\Delta t} V_s^{n+1} \right. \right. \right. \\ \left. \left. - \frac{1}{2\Delta t} I_s^{n+1} V^{n-1} + R_{GCL}^{n+1} \right) \cdot C_s^{n+1} \cdot \Lambda_s^{n+1} \right] \\ \left. + [I_s^{n+2}]^T \left[ \left( \frac{c}{\Delta t} I_s^{n+2} V^n \right) \cdot C_s^{n+2} \cdot \Lambda_s^{n+2} \right] \right. \\ \left. + [I_s^{n+3}]^T \left[ \left( \frac{d}{\Delta t} I_s^{n+3} V^n \right) \cdot C_s^{n+3} \cdot \Lambda_s^{n+3} \right] \right\} \end{aligned}$$

- The time-dependent adjoint equations are considerably more complex than the Navier-Stokes equations
- Total FUN3D implementation consists of nearly 1 million lines of code
- Tremendous amount of software infrastructure required



Page 1 of 4 of the adjoint equations derived and implemented in:

Nielsen, E.J., and Diskin, B., "Discrete Adjoint-Based Design for Unsteady Turbulent Flows on Dynamic Overset Unstructured Grids," *AIAA Journal*, Vol. 51, No. 6, June 2013.



# Challenges for Unsteady Problems

- Extensive linearization and infrastructure effort, particularly for dynamic and overset grids
- Sheer cost – every simulation is now a time-dependent run
  - For steady flows, terms could be computed once and stored for efficiency
  - Unsteady flows require these linearizations to be recomputed at every time step
- Need for entire forward solution
  - Brute force it: Store to disk (big data)
  - Recompute it: Store periodically, recompute intermediate steps as needed (checkpointing)
  - Approximate it: Store periodically, interpolate intermediate steps as needed
- Chaotic flows





- The amount of data adds up fast – consider an example:
  - 50,000,000 grid points and 10,000 physical time steps
  - Using a 1-equation turbulence model (6 unknowns per grid point)
  - Dynamic grids (3 additional unknowns per grid point)
    - $50,000,000 \times 10,000 \times (6+3) \times 8 \text{ bytes} = 36 \text{ Terabytes}$
- This amount of data has not been prohibitively large for our resources, but it is a lot (and we need to go much bigger)
- So far, the challenge has been efficiently getting the data to/from the disk at every single time step
- Implemented sophisticated parallel asynchronous I/O mechanisms
  - Data is brought in for the next time step during current time step








# Verification of Implementation

## Problem Definition

- Fully turbulent flow:  $M_\infty=0.1$ ,  $\alpha=2^\circ$ ,  $Re=1M$ ,  $\mu=0.12$
- Composite grid consists of six component grids
- All verification cases run on 360 cores



Component	Topology	Motion	Motion Paradigm	Ancestry
Domain	Hex (Cartesian)	Inertial	Static	Great-grandparent
Fuselage	Prz/pyr/tet	Rotation, translation	Rigid	Grandparent
Blades	Tet	Azimuthal rotation	Rigid	Parent
Blades	-	1° vertical oscillatory rotation about hub	Deforming	Child
<b>Total Composite Grid</b>	<b>1,033,243 nodes 3,190,160 elements Hex/prz/pyr/tet</b>	-	<b>Deforming</b>	<b>Four generations</b>



# Verification of Implementation

*Compressible Results Shown; Incompressible Also Available*

Adjoint Result    Complex Variable Result ( $\varepsilon=1 \times 10^{-50}$ )

*All equation sets converged to machine precision*

	$\partial C_L / \partial \mathbf{D}$ After 5 Physical Time Steps			
Design Variable	BDF1	BDF2	BDF2opt	BDF3
Angle of Attack	0.032387388401060 0.032387388401060	0.032390834852470 0.032390834852468	0.032382969025224 0.032382969025223	0.032374960728472 0.032374960728471
Rot Rate Blade 1	0.049010917009587 0.049010917009599	0.049303058989982 0.049303058989996	0.049392787479850 0.049392787479863	0.049505103043920 0.049505103043932
Shape Blade 2	-0.004741396075215 -0.004741396075140	-0.005822463933444 -0.005822463933378	-0.005891431208194 -0.005891431208081	-0.006004976330078 -0.006004976329965
Flap Freq Blade 3	-0.117898939551988 -0.117898939551986	-0.117819415724222 -0.117819415724217	-0.117766926835991 -0.117766926835985	-0.117703857525237 -0.117703857525232
Rot Rate Fuselage	0.069017024693610 0.069017024693502	0.064234646041659 0.064234646041451	0.064468559766846 0.064468559764283	0.064688175664501 0.064688175664242
Trans Rate Fuselage	-0.002337944913071 -0.002337944913072	-0.002888267191799 -0.002888267191802	-0.002909479741304 -0.002909479741305	-0.002940703514842 -0.002940703514857
Shape Fuselage	-0.000035249806854 -0.000035249806854	-0.000039222298162 -0.000039222298162	-0.000039485944155 -0.000039485944155	-0.000039831885096 -0.000039831885096




# ***Examples***

## ***Forward / Reverse Solutions for F-15***



***Forward  
Solution***

- Transonic turbulent flow over modified F-15 configuration
- Propulsion effects included as well as simulated aeroelastic deformations of canard/wing/h-tail
- Objective is lift-to-drag ratio



***Reverse  
Solution***






- Incompressible turbulent flow over NREL Phase VI wind turbine
- Overset grids used to model rotating blade system
- Objective function is based on the torque



**Forward Solution**

**Reverse Solution**








# Adjoint-Based Mesh Adaptation

*Collaboration with Venditti / Darmofal of MIT*

- **Objective:** Adapt grid to compute drag on lower airfoil as accurately as possible
- **Result of adjoint-based adaptation:**
  - Uniformly-resolved shocks are not required
  - Drag is computed accurately with a 90% smaller grid



Feature-Based Adaptation  
 $C_D=0.0767$  37,352 Nodes




Adjoint-Based Adaptation  
 $C_D=0.0766$  3,810 Nodes






# *Mesh Adaptation for Jet Plume*


**Baseline Mesh**




**Adapted Mesh**



**Baseline Solution**



**Adapted Solution**




- Quarter of axisymmetric domain modeled;  $M_\infty=2.2$ ,  $Re_D=1.86M$
- Adjoint objective function is integrated pressure signal at 1D distance
- Mesh adapted from 1.3M nodes to 2.9M nodes






# *Mesh Adaptation for Jet Plume*


**Baseline Mesh**




**Adapted Mesh**



**Baseline Solution**





**Adapted Solution**





# *Mesh Adaptation for SBLI*







- Part of SBLI workshop at 2010 AIAA Orlando ASM conference
- $M_\infty=2.25$ ,  $Re=5683/cm$
- Adjoint objective function is drag on lower wall
- Mesh adapted from 0.7M nodes to 1.3M nodes





# *Mesh Adaptation for SBLI*







Langley Research Center

# ***Mesh Adaptation for HLPW-1***

***Held at 2010 AIAA Summer Meeting in Chicago***







Langley Research Center

# ***Mesh Adaptation for HLPW-1***

***Held at 2010 AIAA Summer Meeting in Chicago***



**Coarse Workshop Mesh**




**Adapted Mesh**






# ***Mesh Adaptation for HLPW-1***


***Held at 2010 AIAA Summer Meeting in Chicago***



**Coarse Workshop Mesh**



**Adapted Mesh**










# ***Mesh Adaptation for HLPW-1***


***Held at 2010 AIAA Summer Meeting in Chicago***



**Coarse Workshop Mesh**



**Adapted Mesh**










# ***Mesh Adaptation for HLPW-1***

***Held at 2010 AIAA Summer Meeting in Chicago***



**Adjoint-Based Adaptation Parameter**








# ***Mesh Adaptation for HLPW-1***

***Held at 2010 AIAA Summer Meeting in Chicago***










Langley Research Center

# ***Adjoint-Based Mesh Adaptation***

***Other Applications***









# *Design of AFC for High-Lift*



- Objective: Maximize lift using all available parameters
- Design variables include
  - External wing shape
  - Jet blowing parameters
  - Jet incidence and location
  - Relative location of slat/main/flap
- Designs performed using 2,048 cores for ~5 days per run
- Mean value of lift increased by 27%




Jet Incidence



Shape Deformation







Jet Sliding



Relative Translation  
And Rotation



# Design of AFC for High-Lift







# ***Biologically-Inspired Flapping Wing***

## ***Overview***



- Simple wing geometry with kinematic motion based on Hawkmoth insect
  - Screen represents plane of symmetry
- Composite mesh totals 8,355,344 nodes / 49,088,120 tetrahedra
- Wing operates at 26 Hz in quiescent conditions with  $Re=1,280$
- Governing equations: incompressible laminar N-S
- Kinematics consist of  $\pm 60^\circ$  sweeping and  $\pm 45^\circ$  feathering motions
- Net result of motion is a thrust force in the upward direction
- BDF2opt scheme run for 5 periods with 50 subiterations and 250 steps/period



# Biologically-Inspired Flapping Wing


## Problem Definition

- Motion transform matrix  $\mathbf{T}^n$  specified via user-defined kinematics interface:

$$\theta_x^n = A_x [\cos(\omega_{1x}t) - 1] + B_x \sin(\omega_{2x}t) \Rightarrow \mathbf{T}_x^n$$


$$\theta_y^n = A_y [\cos(\omega_{1y}t) - 1] + B_y \sin(\omega_{2y}t) \Rightarrow \mathbf{T}_y^n$$

$$\theta_z^n = A_z [\cos(\omega_{1z}t) - 1] + B_z \sin(\omega_{2z}t) \Rightarrow \mathbf{T}_z^n$$



$$\mathbf{T}^n = \mathbf{T}_z^n \mathbf{T}_y^n \mathbf{T}_x^n$$

- Thrust profile shows 2/cyc behavior



Goal is to maximize  $\bar{C}_T$  over final period using two different objective functions:

$$f = \sum_{n=1,001}^{1,250} (C_T^n - 5.0)^2 \Delta t$$

Distribution function

$$f = \left[ \left( \frac{1}{250} \sum_{n=1,001}^{1,250} C_T^n \right) - 5.0 \right]^2 \Delta t$$

Time-average function

Design variables: 3 coords of rotation center, 12 kinematic parameters  $A$ ,  $B$ ,  $\omega_1$ ,  $\omega_2$





# Biologically-Inspired Flapping Wing

## Results

- Very moderate changes to all design variables
- Both designs now yield three peaks in cost interval
- Shape optimization using 88 parameters describing twist/shear/thickness/camber also attempted; opposing effects during sweeping negate improvements

	$\bar{C}_T$	Flow Solves (4 hrs)	Adjoint Solves (3 hrs)	Total Time
Baseline	0.127	-	-	-
Distribution Function	0.207	22	10	5 days (227,000 CPU hrs)
Time-average Function	0.265	25	8	5+ days (238,000 CPU hrs)








Langley Research Center


# ***Biologically-Inspired Flapping Wing***

## ***Baseline and Optimal Flow Fields***

Isosurfaces of Vorticity Colored by Pressure



Baseline



Optimal  
(Time-Average Function)



# ***UH-60A Blackhawk Helicopter***

## ***Overview***



- Composite grid consists of 9,262,941 nodes / 54,642,499 tetrahedra
- Compressible RANS:  $M_{tip}=0.64$ ,  $Re_{tip}=7.3M$ ,  $\mu=0.37$ ,  $\alpha=0.0^\circ$
- Blade pitch has child motion governed by collective and cyclic control inputs:

$$\theta = \theta_c + \theta_{1c} \cos \psi + \theta_{1s} \sin \psi$$

Blade pitch      Collective      Lateral cyclic      Longitudinal cyclic

- Baseline value of all control inputs is zero



# UH-60A Blackhawk Helicopter

## Problem Definition and Results


- Objective is to maximize  $\bar{C}_L$  while satisfying trim constraints over second rev:

$$\min f = \left[ \left( \frac{1}{360} \sum_{n=361}^{720} C_L^n \right) - 2.0 \right]^2 \Delta t \quad \text{such that}$$

$$g_1 = \frac{1}{360} \sum_{n=361}^{720} C_{M_x}^n \Delta t = 0$$

$$g_2 = \frac{1}{360} \sum_{n=361}^{720} C_{M_y}^n \Delta t = 0$$

- Separate adjoint solutions required for all three functions
- 67 design variables include 64 thickness and camber variables across the blade planform, plus collective and cyclic control inputs up to  $\pm 7^\circ$



	$\bar{C}_L$	Flow Solves (2 hrs)	Adjoint Solves (3 hrs)	Total Time
Baseline	0.023	-	-	-
Design	0.103	4	4	0.8 days (38,400 CPU hrs)





- Feasible region is quickly located
- Both moment constraints are satisfied within tolerance at the optimal solution
- Final controls:  $\theta_c=6.71^\circ$ ,  $\theta_{1c}=2.58^\circ$ ,  $\theta_{1s}=-7.00^\circ$





# ***UH-60A Blackhawk Helicopter***

## ***Results***






# Multidisciplinary Design

## Sonic Boom Mitigation

- Multidisciplinary discrete adjoint has been very successful for sonic boom mitigation - discrete derivatives of ground-based metrics with respect to OML
- Many other disciplines being considered / pursued





# The Chaos Problem

**Compute sensitivities of infinite time averages  
for chaotic flows (DES, HRLES, LES, etc)**



- Theory exists that states these sensitivities are well-defined and bounded

## Why does conventional approach not work?

For chaotic flows:

- The finite time average approaches the infinite time average
- The sensitivity for a finite time average does not approach the sensitivity for the infinite time average

*Chaotic shedding for 0012*  
 $M_\infty=0.1$   $Re=10,000$   $\alpha=20^\circ$







- Least-Squares Shadowing (LSS) method proposed by Wang and Blonigan
  - Key assumption is ergodicity of the simulation: long time averages are essentially independent of the initial conditions
  - Also assumes existence of a shadowing trajectory
- The LSS formulation involves a linearly-constrained least squares optimization problem which results in a set of optimality equations
- Preliminary LSS exploration for fluids applications

***Define the following quantities:***


$Q_i \equiv$  Vector of conserved variables at time level  $i$

$R_i \equiv$  Vector of spatial residuals at time level  $i$

$V \equiv$  Matrix of cell volumes

$t \equiv$  Time

$f_i \equiv$  Objective function at time level  $i$



$$\mathbf{G} = \mathbf{V}/\Delta t + \partial \mathbf{R} / \partial \mathbf{Q}$$

$$\mathbf{g} = \partial f / \partial \mathbf{Q}$$

$h$  is related to time dilation

$\alpha$  is a regularization parameter

***This is a globally coupled space-time problem, where each sub-row represents a time level***



# *Reduced LSS System*

- To determine sensitivities, we need the LSS adjoint solution
- Use a Schur complement approach to arrive at a reduced system for the LSS adjoint variables:

Writing the previous system as

$$\begin{pmatrix} \mathbf{V} & 0 & \mathbf{B}^T \\ 0 & \alpha^2 \mathbf{I} & \mathbf{C}^T \\ \mathbf{B} & \mathbf{C} & 0 \end{pmatrix} \begin{pmatrix} \Phi \\ \Psi \\ \Lambda \end{pmatrix} = - \begin{pmatrix} \mathbf{g} \\ \mathbf{h} \\ 0 \end{pmatrix}$$

The LSS adjoint solution can be determined from

$$\left[ \mathbf{B}\mathbf{V}^{-1}\mathbf{B}^T + \frac{1}{\alpha^2} \mathbf{C}\mathbf{C}^T \right] \Lambda = -\mathbf{B}\mathbf{V}^{-1}\mathbf{g} - \frac{1}{\alpha^2} \mathbf{C}\mathbf{h}$$



- This remains a globally coupled space-time problem
- $\mathbf{B}\mathbf{B}^T$  increases the fill of the matrix
- Furthermore, the system is dense due to  $\mathbf{C}\mathbf{C}^T$  term





# ***Problem Definition***

Shedding NACA 0012  
 $M_\infty=0.1$   $Re=10,000$   $\alpha=20^\circ$




- Unstructured mesh consisting of 102,940 grid points with 100,139 prisms and 1,144 hexes in spanwise direction
- Relatively coarse wall spacing to alleviate stiffness in LSS system
- Laminar Navier-Stokes equations with second-order spatial discretization
- First-order backward differencing in time for LSS simplicity




# Problem Definition

## *Instantaneous Lift vs Time*



## *Finite Time Average of Lift vs Alpha*



- To improve ergodicity, simulation started from chaotic initial solution (generated by 2,000 steps from free stream)
- Objective is to maximize time-averaged lift over final 1,000 time steps



- Execute FUN3D flow/adjoint solvers to output data to disk for use in LSS: nonlinear residual vectors and Jacobians of residual and objective function
- For this tiny problem, the raw dataset is ~1.1 TB (in-core requirement much larger)
- Developed standalone LSS solver, where partitioning is performed in time with a single time plane per core
  - For simplicity, the spatial discretization fits on a single core
  - Spatial decompositions are possible but not considered here
- Global GMRES solver used with a local ILU(0) preconditioner for each time plane, with  $CC^T$  term neglected in preconditioner
- Execution was constrained to a subset of the cores available on each 128 GB Haswell node to provide sufficient memory for solving the LSS adjoint system
- Checked discrete consistency of LSS implementation using complex variables
- This complex variable test does not provide the same rigor for LSS as for conventional adjoint implementations; additional verification approaches needed







# ***Solution of LSS Adjoint System***

- After ~30 minutes for I/O, solution converges 5 orders of magnitude in ~30 mins on 2,000 cores
- Solution remains bounded
- Just tip of the iceberg – how will we extend to billions of mesh points with millions of time steps?

***Convergence of LSS Adjoint System***



***LSS Adjoint Solution for Energy Equation***





# ***Thank You For Having Me!***

- Always interested in new collaborations – need help in numerous areas
- Please do not hesitate to get in touch about opportunities at Langley

**Eric.J.Nielsen@nasa.gov**

***<http://fun3d.larc.nasa.gov>***

